

1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product name: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio

350P

Part number: LEXE450DR

1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Laser Printers

1.3 **SUPPLIER DETAILS**

Supplier: Clover Imaging Group

4200 Columbus Street Ottawa, IL 61350 United States

Phone number: 815-431-8100

Fax: 815-461-8583

Contact Hours: 08:00AM-05:00PM CST

1.4 EMERGENCY TELEPHONE NUMBERS

Supplier: 815-431-8100

* This document provides safety-related information about ink/toner, in various forms, for use in copiers/printers etc.

2. HAZARDS IDENTIFICATION

2.1 INFORMATION and CLASSIFICATION

Overview: Classification of the substance or mixture: Directive 1999/45/EC - Not listed; Regulation GHS - Not

listed.

2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: N/A
Risk Phrases: N/A
Safety Phrases: N/A

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Revision date: 05/31/2015 Page: 1/9



3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	OSHA	ACGIH	Other
			PEL	TLV	
Aluminum Tube	7429-90-5	70-80			
Organic Sensitive Material	TRADE SECRET	<1.5			Private information
Gear	TRADE SECRET	20-30			Private information.
			There are		Harmful substance is not contained
			no exposure		in this OPC Drum.
			limits		
			identified		
			for this		
			product.		

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the specified substance/mixture.

4. FIRST-AID MEASURES

4.1 FIRST AID MEASURES

4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: Not applicable. It does not correspond to the following matters in case of use for proper purpose.

Eye contact: Not applicable. It does not correspond to the following matters in case of use for proper purpose.

Skin contact: Not applicable. It does not correspond to the following matters in case of use for proper purpose.

Ingestion: Not applicable. It does not correspond to the following matters in case of use for proper purpose.

4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A
Immediate Medical Attention Required: N/A

4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: N/A
Delayed Symptoms from Exposure: N/A

4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

N/A

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Revision date: 05/31/2015 Page: 2/9



5. FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Recommended Extinguishing Media: water spray, CO2, Powders, foam

Extinguishing Media Not to be Used: Do not use water jet.

5.2 **SPECIAL HAZARD**

Unusual Fire/Explosion Hazards: Exposure to decomposition products may cause a health hazard. Hazardous

Revision date: 05/31/2015

decomposition and/or combustion products: CO, CO2, smoke

Extinguishing Media Not to be Used: N/

5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective clothing and wear self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

N/A

6.1.2 ADDITIONAL FIRST AID INFORMATION

N/A

6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: N/A

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Page: 3/9



7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed. If toner, avoid

creating dust. Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

7.3 **SPECIFIC END USES**

Printing devices

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.2 **EXPOSURE CONTROLS**

Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

Eye/Face Protection:

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

Additional Protection:

N/A

Protective Clothing and Equipment:

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splashproof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

Safety Stations:

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment:

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Revision date: 05/31/2015

Page: 4/9

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 **DETAIL INFORMATION**

Physical state: APPEARANCE: Solid coated by organic sensitive substance, which plastic gear were equipped to

the aluminum substrate.

Color: Black
Odor: Odorless.

Odor threshold: N/A

Boiling point: N/A

Melting point: N/A

Flash point: N/A

Explosion limits: N/A

Relative density: N/A

Auto-ignition temperature: N/A

9.2 OTHER INFORMATION

SOLUBILITY: Insoluble.

10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

Revision date: 05/31/2015

Page: 5/9

polymerization will not occur.

10.3 Hazardous Polymerization: Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidizing materials

10.6 Hazardous Decomposition: Will not occur.



11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: N/A
Acute Toxicity: N/A
Skin Corrosion/Irritation: N/A
Serious Eye Damage: N/A
Inhalation: N/A
Sensitization: N/A

Mutagenicity: Ames test is negative.

Carcinogenicity: No data available. Not classified or listed by IARC, ACGIH, OSHA, NTP, ILO.

Reproductive Toxicity: N/A STOT - Single Exposure: N/A **STOT - Multiple Exposure:** N/A Ingestion: N/A **Hazard Class Information:** N/A Mixture on Market Data: N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A Not Meeting Classification: N/A Routes of Exposure: N/A **Interactive Effects:** N/A **Absence of Specific Data:** N/A Mixture vs Substance Data: N/A

12. ECOLOGICAL INFORMATION

12.1 Eco toxicity: N/A

12.2 **Degradability:** N/A

12.3 Bioaccumulation Potential: N/A

12.4 Mobility in Soil: N/A

12.5 PBT & vPvB Assessment: N/A

12.6 Other Adverse Effects: N/A

13. DISPOSAL CONSIDERATIONS

Disposal Information:

Dispose of product in accordance with local authority regulations.

Empty container retains product residue.

Physical/Chemical Properties that affect Treatment:

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

Waste Treatment Information:

If toner, do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

Revision date: 05/31/2015

Personal Protection Required:

N/A

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Page: 6/9



Revision date: 05/31/2015

14. TRANSPORT INFORMATION

14.1 **ID Number:** N/A

14.2 Shipping Name: N/A

14.3 Hazard Class: N/A

14.4 Packing Group: N/A

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport: N/A

15. REGULATORY INFORMATION

15.1 **Regulatory Information:** Application Law: None

EPA Regulatory Information: N/A

CERCLA Reportable Quantity: N/A

15.2 Superfund Information:

Hazard Categories:

Immediate: N/A

Delayed: N/A

Fire: N/A

Pressure: N/A

Reactivity: N/A

Section 302 - Extremely Hazardous: N/A

Section 311 - Hazardous: N/A

15.3 State Regulations: N/A

15.4 Other Regulatory Information: N/A

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Page: 7/9



16. OTHER INFORMATION

General Comments: This information is based on our current knowledge. It should not therefore be construed as

Revision date: 05/31/2015

guaranteeing specific properties of the products as described or their suitability for a particular

application

Creation Date of this SDS: 07/22/2020

Product: Universal Drum Unit for Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P Page: 8/9



Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	NIOSH = National Institute for Occupational Safety and Health			
Hygienists				
CERCLA = Comprehensive Environmental Response Compensation	OSHA = Occupational Health and Safety Administration			
and Liability Act				
CLP = Classification, Labeling, and Packaging	PEL = Permissible Exposure Limit			
DSD = Dangerous Substances Directive	SCBA = Self Contained Breathing Apparatus			
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity			
GHS = Globally Harmonized System	TLV = Threshold Limit Value			
N/A = Not Applicable	UK = United Kingdom			
NFPA = National Fire Protection Association	UN = United Nations			

DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only.
These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers.
This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Revision date: 05/31/2015

Product: Universal Drum Unit for

Lexmark E250/E350/E352/E450, Dell 1720/1720DN, IBM 1612, Toshiba e-Studio 350P