

1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product name: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466

Part number: LEXE460LC

1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Laser Printers

1.3 SUPPLIER DETAILS

Supplier: Clover Imaging Group

4200 Columbus Street Ottawa, IL 61350 United States

Phone number: 815-431-8100

Fax: 815-461-8583

Contact Hours: 08:00AM-05:00PM CST

1.4 EMERGENCY TELEPHONE NUMBERS

Supplier: 815-431-8100

2. HAZARDS IDENTIFICATION

2.1 INFORMATION and CLASSIFICATION

Overview: Hazard information: Primary Routes of Exposure: Dust inhalation, skin contact. Inhalation: Low acute

Revision date: 06/09/2015

inhalation toxicity. As with exposure to high concentrations of any dust, minimal irritation of the respiratory tract may occur. Exposure not probable with intended use. Chronic - No adverse changes in the lungs result from this accumulation. Exposure not probable with intended use. Skin contact: Not an irritant. Low dermal toxicity. Not a dermal sensitizer. Eye contact: Toner may act as a mechanical

irritant. Ingestion: Low acute oral toxicity.

2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: N/A
Risk Phrases: N/A
Safety Phrases: N/A

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Page: 1/9

^{*} This document provides safety-related information about ink/toner, in various forms, for use in copiers/printers etc.



3. COMPOSITION / INFORMATION ON INGREDIENTS

| Ingredients | CAS number | Weight % | OSHA PEL | ACGIH TLV | Other |
|----------------------|--------------|----------|-------------|--------------|-----------------------|
| Polyester Resin | TRADE SECRET | 65-85 | None | None | NJTSRN 80100286-6001P |
| Iron Oxide | 1317-61-9 | 7-13 | None | None | |
| Carbon Black | 1333-86-4 | 5-10 | 3.5 mg/m3 | 3.5 mg/m3 | |
| | | | 8 hours | 8 hours | |
| | | | TWA | TWA | |
| Amorphous Silica | TRADE SECRET | 1-3 | None | None | NJTSRN 80100451-5015 |
| (modified) | | | | | |
| Polymer Wax | TRADE SECRET | 1-5 | None | None | NJTSRN 80100451-5016 |
| Titanium Dioxide | 13463-67-7 | 0.1-1 | 15 mg/m3 8 | 10 mg/m3 8 | |
| | | | hours TWA | hours TWA | |
| Charge Control Agent | TRADE SECRET | 0.5-1.5 | None | None | NJTSRN 80100451-5037 |

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the specified substance/mixture.

4. FIRST-AID MEASURES

4.1 FIRST AID MEASURES

4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: If symptoms, such as shortness of breath or persistent coughing are experienced, remove source

of contamination and move individual to fresh air. If symptoms persist, seek medical attention.

Eye contact: Do not rub eyes. Flush immediately with plenty of water. Remove contact lenses and continue

flushing for at least 15 minutes. If irritation develops and persists, seek medical attention.

Skin contact: Wash with soap and water. Should irritation occur, seek medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical

attention if symptoms appear.

4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A
Immediate Medical Attention Required: N/A

4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: Aggravated conditions: Exposure to high airborne dust concentrations, including toner,

Revision date: 06/09/2015

may aggravate existing respiratory conditions.

Delayed Symptoms from Exposure: N/A

4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

Notes to physician: No specific antidote.

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Page: 2/9



5. FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Recommended Extinguishing Media: Carbon dioxide, water spray or fog, dry chemical or foam.

Extinguishing Media Not to be Used: N/A

5.2 **SPECIAL HAZARD**

Unusual Fire/Explosion Hazards: Like many finely divided materials, toner dust, in high concentrations can form an

explosive mixture in air which, if ignited, could result in a dust explosion. Hazardous combustion products: Carbon monoxide, carbon dioxide, unidentified organics.

Extinguishing Media Not to be Used: N/A

5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective clothing and wear self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

None required for intended use in printer.

6.1.2 ADDITIONAL FIRST AID INFORMATION

N/A

6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: If a dust cloud is possible due to a spill, remove all sources of ignition such as open sparks,

flames, or static discharge to prevent the ignition of the dust. Minimize dust generation during clean up. Sweep up spill with non-metallic broom and dustpan. Contain for disposal. Oil permeated sweeping compound may be useful in cleaning up spills. Disposal is subject to

Page: 3/9

national, state, regional, or provincial regulations.

Revision date: 06/09/2015



7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed. If toner, avoid

creating dust. Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

7.3 **SPECIFIC END USES**

Printing devices

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.2 **EXPOSURE CONTROLS**

Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

Eye/Face Protection:

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

Additional Protection:

N/A

Protective Clothing and Equipment:

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splashproof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

Safety Stations:

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment:

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Revision date: 06/09/2015

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Page: 4/9



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 **DETAIL INFORMATION**

Physical state: PHYSICAL STATE: Solid (Toner Cartridge). APPEARANCE: Black.

Color: Black

Odor: Faint odor (Plastic.)

Odor threshold: N/A

Boiling point: N/A

Melting point: Not determined.

Flash point: Solid, not applicable.

Explosion limits: N/A
Relative density: N/A
Auto-ignition temperature: N/A

9.2 OTHER INFORMATION

SOLUBILITY: Insoluble in water.

10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

Revision date: 06/09/2015

polymerization will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidizing materials

10.6 Hazardous Decomposition: Will not occur.

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Page: 5/9



11. INFORMATION ON TOXICOLOGICAL EFFECT

Toner dust is a particulate not otherwise classified (PNOC) or regulated (PNOR). Mixtures:

Ingestion: Low acute oral toxicity. Exposure not probable with intended use. Acute toxicity oral rat **Acute Toxicity:**

LD50 (mg/kg): >5000.

Skin Corrosion/Irritation: N/A Serious Eye Damage: N/A

Inhalation: Low acute inhalation toxicity. As with exposure to high concentrations of any dust, minimal

irritation of the respiratory tract may occur. Pure Carbon Black and Titanium Dioxide, minor components of this product, has been listed by IARC as a group 2B (possible carcinogen). This classification is based on rat "lung particulate overload" studies performed with airborne particulate. Toner is not listed by IARC, NTP, or OSHA, Long term exposure to excessive

concentrations of iron oxide-containing dusts has resulted in a condition identified as siderosis, a relatively benign pneumoconiosis, caused by deposition of iron oxide particles in the lung.

Sensitization: N/A **Mutagenicity:** N/A

Carcinogenicity: Classified 2B (Possible for humans.) by IARC [Carbon Black]. Classified 2B (Possible for humans.)

Revision date: 06/09/2015

Page: 6/9

by IARC [Titanium Dioxide].

Reproductive Toxicity: N/A

Aggravating conditions: Exposure to high airborne dust concentrations, including toner, may STOT - Single Exposure:

aggravate existing respiratory conditions.

STOT - Multiple Exposure: N/A

N/A

Ingestion: **Hazard Class Information:** N/A Mixture on Market Data: N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A Not Meeting Classification: N/A

Routes of Exposure: Inhalation of dust, skin contact,

Interactive Effects: N/A Absence of Specific Data: N/A Mixture vs Substance Data: N/A

12. ECOLOGICAL INFORMATION

12.1 Eco toxicity: N/A

Not determined. 12.2 Degradability:

12.3 Bioaccumulation Potential:

Not determined. 12.4 Mobility in Soil:

12.5 PBT & vPvB Assessment: N/A

12.6 Other Adverse Effects: None known.

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466



13. DISPOSAL CONSIDERATIONS

Disposal Information:

Dispose of product in accordance with local authority regulations.

Empty container retains product residue.

Physical/Chemical Properties that affect Treatment:

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

Waste Treatment Information:

If toner, do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

Personal Protection Required:

N/A

14. TRANSPORT INFORMATION

14.1 **ID Number:** Not regulated by any transport mode.

14.2 **Shipping Name:** Not regulated by any transport mode.

14.3 **Hazard Class:** HMIS Classification: Health: 1* Flammability: 1 Reactivity: 0

14.4 **Packing Group:** Not regulated by any transport mode.

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport: N/A

15. REGULATORY INFORMATION

15.1 **Regulatory Information:** TSCA (USA): All ingredients are listed on the Toxic Substances Control Act (TSCA)

inventory, have been registered, or are exempt. SARA/ EPCRA (USA): None of the ingredients in this product has a final reportable quantity (RQ) under Emergency Planning and Community Right-to Know Act (EPCRA)- Section 302: Extremely Hazardous Substances

(EHS) or notification requirements for EHS under Section 304.

EPA Regulatory Information: N/A

CERCLA Reportable Quantity: N/A

15.2 Superfund Information:

Hazard Categories:

Immediate: N/A

Delayed: N/A

Fire: NFPA Rating: Health: 1 Flammability: 1

Reactivity: 0

Pressure: N/A

Reactivity: N/A

Section 302 - Extremely Hazardous: N/A

Section 311 - Hazardous: N/A

Cartridge for Lexmark Compliant E460/E462/X463/X464/X466

15.3 **State Regulations:** California Prop. 65: This product contains no known materials at levels which the State of

California has found to cause cancer, birth defects or other reproductive harm.

Product: Extra High Yield Toner Revision date: 06/09/2015

Page: 7/9



15.4 Other Regulatory Information:

International regulations lists: EINECS (Europe) - All ingredients are listed on the European Inventory of Existing Commercial Substances (EINECS) list, have been registered on the European List of New Chemical Substances (ELINCS), or are exempt; ENCS (Japan) - All ingredients are listed on the Japanese Existing and New Chemical Substances (ENCS) list, have been registered, or are exempt; AICS (Australia) - All ingredients are listed in Australian Inventory of Chemical Substances (AICS), have been registered, or are exempt; Philippines inventory (PICCS) - All ingredients are listed on the Philippines Inventory (PICCS) or are exempt; Korea inventory (KECI) - All ingredients are listed on the Korean Existing Chemicals List (ECL), have been registered, or are exempt; China inventory (IECSC) - All ingredients are listed on the Chinese inventory (IECSC) or are exempt. Canada: WHMIS (Canada) - Not controlled under WHMIS (Canada); DSL/NDSL - All ingredients are listed on the Canadian Domestic Substances List (DSL), have been registered on the Non-Domestic Substances List (NDSL), or are exempt. Mexico Classification: Health: 1 Flammability: 1 Reactivity: 0.

16. OTHER INFORMATION

General Comments: This information is based on our current knowledge. It should not therefore be construed as

Revision date: 06/09/2015

quaranteeing specific properties of the products as described or their suitability for a particular

application

Creation Date of this SDS: 07/23/2020

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Page: 8/9



Key to Abbreviations and Acronyms used in this sheet:

| ACGIH = American Conference of Governmental Industrial | NIOSH = National Institute for Occupational Safety and Health |
|--|---|
| Hygienists | |
| CERCLA = Comprehensive Environmental Response Compensation | OSHA = Occupational Health and Safety Administration |
| and Liability Act | |
| CLP = Classification, Labeling, and Packaging | PEL = Permissible Exposure Limit |
| DSD = Dangerous Substances Directive | SCBA = Self Contained Breathing Apparatus |
| EPA = Environmental Protection Agency | STOT = Specific Target Organ Toxicity |
| GHS = Globally Harmonized System | TLV = Threshold Limit Value |
| N/A = Not Applicable | UK = United Kingdom |
| NFPA = National Fire Protection Association | UN = United Nations |
| | |
| | |
| | |
| | |

DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only.

These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Product: Extra High Yield Toner Cartridge for Lexmark Compliant E460/E462/X463/X464/X466 Revision date: 06/09/2015 Page: 9/9