

#### 1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

#### 1.1 PRODUCT IDENTIFIER

Product name: High Yield Black Toner Cartridge for Lexmark C736/X736/X738

LEXC736B Part number:

#### 1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Laser Printers

1.3 SUPPLIER DETAILS

Clover Imaging Group Supplier:

> 4200 Columbus Street Ottawa, IL 61350 **United States**

Phone number: 815-431-8100

Fax: 815-461-8583

08:00AM-05:00PM CST Contact Hours:

### 1.4 EMERGENCY TELEPHONE NUMBERS

815-431-8100 Supplier:

### 2. HAZARDS IDENTIFICATION

#### 2.1 INFORMATION and CLASSIFICATION

Product is a stable, non-flammable powder. If used as intended, the product does not present an acute Overview:

or chronic health problem. This health hazard assessment is based on information that is available on the properties of its components. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. Fine toner dust clouds may form explosive mixtures with air. Classification According to Directive 1272/2008/EC: Not classified.

Hazard Classes: Not Classified.

## 2.2 **LABEL ELEMENTS**

Applicable Pictograms:

PICTOGRAM

**Danger Indications:** N/A Risk Phrases: None Safety Phrases: N/A

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Revision date: 05/01/2018 Product: High Yield Black Toner Page: 1/9

Cartridge for Lexmark C736/X736/X738

<sup>\*</sup> This document provides safety-related information about ink/toner, in various forms, for use in copiers/printers etc.



#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	OSHA	ACGIH	Other
			PEL	TLV	
Polyester Resin	27136-00-1	≤95	Not Listed	Not Listed	
Carbon Black	1333-86-4	<8	3.5 mg <sup>3</sup>	3.5 mg <sup>3</sup>	EC NUMBER: 215-609-9, REACH
					NUMBER: 05-2116645306-46-0000
Polyolefin Wax	25085-53-4	<8	15 mg/m³	10 mg/m³	
Charge Control Agent	8050-02-5	<3	Not Listed	Not Listed	
Amorphous Silica	67762-90-7	<3		10.0 mg/m3	
reaction product of 3,5-di-	226996-19-6	<0.1	Not Listed	Not Listed	EC NUMBER: 430-610-6; INDEX
tert-butylsalicylic					NUMBER: 040-003-00-4; Hazard
					Classes: Aquatic Acute 1;Aquatic
					Chronic 1; INGREDIENT HAZARD
					PHRASES: H400 Very toxic to
					aquatic life. H410 Very toxic to
					aquatic life with long lasting
					effects.
			TWA: 15	TWA: 10	
			mg/m3	mg/m3	
			(Total dust),	(Inhalable	
			5 mg/m3	particulate),	
			(Respirable	3 mg/m3	
			fraction)	(Respirable	
				particulate)	

The Full Text for all R-Phrases are Displayed in Section 16

#### **COMPOSITION COMMENTS**

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the specified substance/mixture.

### 4. FIRST-AID MEASURES

#### 4.1 FIRST AID MEASURES

#### 4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: Remove to fresh air. If effects occur, consult medical personnel.

Eye contact: Flush eyes immediately with plenty of water for at least 15 minutes.

Skin contact: Flush with plenty of water. Use soap.

Ingestion: No adverse effects anticipated by this route of exposure, incidental to proper handling.

## 4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: No additional information available Immediate Medical Attention Required: No additional information available

#### 4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: No additional information available
Delayed Symptoms from Exposure: No additional information available

#### 4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

Move to Fresh Air

Product: High Yield Black Toner Revision date: 05/01/2018 Page: 2/9 Cartridge for Lexmark C736/X736/X738



#### 5. FIRE-FIGHTING MEASURES

#### 5.1 EXTINGUISHING MEDIA

Recommended Extinguishing Media: Water spray, dry chemical, carbon dioxide or foam type extinguishers.

Extinguishing Media Not to be Used: Full water jet.

5.2 **SPECIAL HAZARD** 

Unusual Fire/Explosion Hazards: Toner material, like most organic material in powder form, is capable of creating a

dust explosion.

Extinguishing Media Not to be Used: N/A

#### 5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective clothing and wear self-contained breathing apparatus

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

### 6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

Minimize the release of particulates. Do not use a vacuum cleaner unless motor is rated dust tight.

#### 6.1.2 ADDITIONAL FIRST AID INFORMATION

Avoid breathing dust.

### 6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

## 6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

## 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: After lightly spraying with water to prevent development of dust, spills should be swept up

Revision date: 05/01/2018

or wiped up. Then residuals can be removed with soap and water. If it is not possible to scrub the floor with water, cover the floor with suitable sheets of paper. These used sheets should be wrapped up in spills and transferred to a suitable container for disposal. Garments may be washed or dry cleaned, after removal of loose toner. Dispose of waste toner in

accordance with local requirements.

Product: High Yield Black Toner Cartridge for Lexmark C736/X736/X738 Page: 3/9



#### 7. HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed. If toner, avoid

creating dust. Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

#### 7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

#### 7.3 **SPECIFIC END USES**

Printing devices

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

### 8.2 **EXPOSURE CONTROLS**

#### Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

### **Eye/Face Protection:**

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

#### Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

#### **Additional Protection:**

N/A

#### **Protective Clothing and Equipment:**

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splashproof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

### **Safety Stations:**

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

#### **Contaminated Equipment:**

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

## Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Product: High Yield Black Toner Revision date: 05/01/2018 Page: 4/9 Cartridge for Lexmark C736/X736/X738



#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 **DETAIL INFORMATION**

Physical state: APPEARANCE: Fine, black powder.

Color: Black

Odor: Almost odorless.

Odor threshold: N/A

Boiling point: N/A

Melting point: > 100 - 150°C (softening point)

Flash point: N/A
Explosion limits: N/A
Relative density: N/A
Auto-ignition temperature: N/A

#### 9.2 OTHER INFORMATION

SPECIFIC GRAVITY: 1.0 - 1.5. SOLUBILITY IN WATER: Negligible solubility in water. This product does not intentionally contain Lead, Mercury, Cadmium, Hexavalent Chromium, Polybrominated Biphenyls (PBBs) or Polybrominated Diphenyl Ethers (PBDEs)

Revision date: 05/01/2018

Page: 5/9

#### 10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidizing materials

10.6 Hazardous Decomposition: Will not occur.

Product: High Yield Black Toner Cartridge for Lexmark C736/X736/X738



#### 11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: Toner contains no known toxicological materials. Product does not contain any 1-nitropyrene,

benzo[a]pyrene, azo dyes or pigments that can release carcinogenic amines.

**Acute Toxicity:** N/A

Skin Corrosion/Irritation: Tests on toners containing similar materials indicate no evidence of acute dermal toxicity. Non-

irritating and non-sensitizing in human patch test.

**Serious Eye Damage:** Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

Inhalation: N/A

Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA Sensitization:

HCS (US).

**Mutagenicity:** Ames Test Negative: Salmonella typhimurium

Carcinogenicity: Carbon black is reclassified as a group 2B by IARC, but inhalation tests using a typical toner

showed no association between toner and animal tumors.

Not classified as toxic according to EU Directive 67/548/EEC and as amended, California **Reproductive Toxicity:** 

Proposition 65, and DFG (Germany).

STOT - Single Exposure: N/A

**STOT - Multiple Exposure:** N/A

Tests on toners containing similar materials indicate no evidence of acute oral toxicity. Ingestion:

**Hazard Class Information:** N/A **Mixture on Market Data:** N/A Symptoms: N/A **Delayed/Immediate Effects:** N/A Test Data on Mixture: N/A **Not Meeting Classification:** N/A **Routes of Exposure:** N/A **Interactive Effects:** N/A

**Absence of Specific Data:** N/A Mixture vs Substance Data: N/A

#### 12. ECOLOGICAL INFORMATION

12.1 Eco toxicity: Based on available data, not harmful to aquatic life.

12.2 Degradability: Not readily biodegradable.

12.3 Bioaccumulation Potential: Bioaccumulation is insignificant.

12.4 Mobility in Soil: Partially soluble in water.

12.5 PBT & vPvB Assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other Adverse Effects: Presents little or no hazard to the environment. Product does not contain any 1-nitropyrene,

Revision date: 05/01/2018

benzo[a]pyrene, azo dyes or pigments that can release carcinogenic amines.

Product: High Yield Black Toner Cartridge for Lexmark C736/X736/X738 Page: 6/9



#### 13. DISPOSAL CONSIDERATIONS

#### **Disposal Information:**

Dispose of product in accordance with local authority regulations.

Empty container retains product residue.

### **Physical/Chemical Properties that affect Treatment:**

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

#### **Waste Treatment Information:**

If toner, do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

### **Personal Protection Required:**

N/A

### 14. TRANSPORT INFORMATION

14.1 **ID Number:** No dangerous goods

14.2 Shipping Name: N/A

14.3 **Hazard Class:** Marine [IMDG]: Not classified as "DANGEROUS GOODS"

14.4 Packing Group: N/A

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport: N/A

## 15. REGULATORY INFORMATION

15.1 **Regulatory Information:** EU 3093/94: Not regulated

EPA Regulatory Information: TSCA: All ingredients are listed on the TSCA Inventory

**CERCLA Reportable Quantity: None** 

15.2 Superfund Information:

**Hazard Categories:** 

Immediate: None

Delayed: None

Fire: None

Pressure: None

Reactivity: None

Section 302 - Extremely Hazardous: Not listed

Section 311 - Hazardous: Not listed

15.3 **State Regulations:** Check each state's regulations that may specifically refer to this product.

15.4 Other Regulatory Information: EEC:1967/548 (1999/45); 1991/689 (2001/118); 1999/13; 2004/42;648/2004; 1907/2006

(REACH); 1272/2008; 75/324/EEC (2008/47/EC); 453/2010/EC

Product: High Yield Black Toner Revision date: 05/01/2018 Page: 7/9
Cartridge for Lexmark C736/X736/X738



## 16. OTHER INFORMATION

**General Comments:** This information is based on our current knowledge. It should not therefore be construed as

Revision date: 05/01/2018

guaranteeing specific properties of the products as described or their suitability for a particular

application

**Creation Date of this SDS:** 07/31/2020

Product: High Yield Black Toner Cartridge for Lexmark C736/X736/X738

Page: 8/9



## Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	NIOSH = National Institute for Occupational Safety and Health			
Hygienists				
CERCLA = Comprehensive Environmental Response Compensation	OSHA = Occupational Health and Safety Administration			
and Liability Act				
CLP = Classification, Labeling, and Packaging	PEL = Permissible Exposure Limit			
DSD = Dangerous Substances Directive	SCBA = Self Contained Breathing Apparatus			
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity			
GHS = Globally Harmonized System	TLV = Threshold Limit Value			
N/A = Not Applicable	UK = United Kingdom			
NFPA = National Fire Protection Association	UN = United Nations			

### DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only.

These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Product: High Yield Black Toner Cartridge for Lexmark C736/X736/X738 Revision date: 05/01/2018 Page: 9/9