

#### 1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

#### 1.1 PRODUCT IDENTIFIER

Product name: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for SATO Printers

Part number: SATOR11041E

#### 1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: Barcode Supplies

1.3 **SUPPLIER DETAILS** 

Supplier: Clover Imaging Group

4200 Columbus Street Ottawa, IL 61350 United States

Phone number: 815-431-8100

Fax: 815-461-8583

Contact Hours: 08:00AM-05:00PM CST

#### 1.4 **EMERGENCY TELEPHONE NUMBERS**

Supplier: 815-431-8100

#### 2. HAZARDS IDENTIFICATION

#### 2.1 INFORMATION and CLASSIFICATION

Overview: Hazard Identification. Human: Not expected to cause harm to humans for its innocuous substance.

Environment: Not available.

#### 2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: N/A
Risk Phrases: N/A
Safety Phrases: N/A

#### 2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Revision date: 10/24/2017 Page: 1/9

<sup>\*</sup> This document provides safety-related information about ink/toner, in various forms, for use in copiers/printers etc.



#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	OSHA PEL	ACGIH TLV	Other
Polyester Resin	25038-59-9	65			
Carbon Black	133-3-86-4	8.5			
Petroleum Resin	68131-77-1	26.5			

The Full Text for all R-Phrases are Displayed in Section 16

#### **COMPOSITION COMMENTS**

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the specified substance/mixture.

### 4. FIRST-AID MEASURES

#### 4.1 FIRST AID MEASURES

#### 4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: n/a

Eye contact: In case of contact, flush eyes immediately with plenty of water and get medical assistance.

Skin contact: Wash with soap and water and get medical assistance if skin irritation occurs.

Ingestion: Ask for immediate medical help.

#### 4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A
Immediate Medical Attention Required: N/A

#### 4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: N/A
Delayed Symptoms from Exposure: N/A

#### 4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

N/A

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Revision date: 10/24/2017 Page: 2/9



#### 5. FIRE-FIGHTING MEASURES

#### 5.1 EXTINGUISHING MEDIA

Recommended Extinguishing Media: Water, carbon dioxide.

Extinguishing Media Not to be Used: N/A

5.2 **SPECIAL HAZARD** 

Unusual Fire/Explosion Hazards: No explosion hazards.

Extinguishing Media Not to be Used: N/A

#### 5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective clothing and wear self-contained breathing apparatus

#### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

#### 6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

Goggles and mask are recommended when particles are released durin slitting process.

#### 6.1.2 **ADDITIONAL FIRST AID INFORMATION**

N/A

#### 6.1.3 **PERSONAL PROTECTION**

Wear personal protective equipment as described in Section 8.

## 6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

## 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Waste should be disposed in accordance with local, state, and federal laws and regulations. Spill or Leak Cleanup Procedures:

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Revision date: 10/24/2017 Page: 3/9



#### 7. HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed. If toner, avoid

creating dust. Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

#### 7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

#### 7.3 **SPECIFIC END USES**

Printing devices

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

#### 8.2 **EXPOSURE CONTROLS**

#### Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

#### **Eye/Face Protection:**

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

#### Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

#### **Additional Protection:**

N/A

#### **Protective Clothing and Equipment:**

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splash-proof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

#### **Safety Stations:**

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

#### **Contaminated Equipment:**

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

### Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Revision date: 10/24/2017 Page: 4/9



#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 **DETAIL INFORMATION**

Physical state: APPEARANCE: Ink coated PET film with black color.

Color: Black

Odor: Little or no odor.

Odor threshold: N/A

Boiling point: N/A

Melting point: >50°C for ink, >250°C for film.

Flash point: >150°C
Explosion limits: N/A
Relative density: N/A
Auto-ignition temperature: N/A

#### 9.2 OTHER INFORMATION

N/A

#### 10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

**Reactivity Hazards:** None **Data on Mixture Substances:** None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

Revision date: 10/24/2017

polymerization will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidizing materials

10.6 Hazardous Decomposition: Will not occur.

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for SATO Printers Page: 5/9



#### 11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: N/A **Acute Toxicity:** N/A Skin Corrosion/Irritation: N/A **Serious Eye Damage:** N/A Inhalation: N/A Sensitization: N/A **Mutagenicity:** N/A Carcinogenicity: N/A **Reproductive Toxicity:** N/A STOT - Single Exposure: N/A **STOT - Multiple Exposure:** N/A Ingestion: N/A **Hazard Class Information:** N/A Mixture on Market Data: N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A Not Meeting Classification: N/A Routes of Exposure: N/A **Interactive Effects:** N/A **Absence of Specific Data:** N/A Mixture vs Substance Data: N/A

#### 12. ECOLOGICAL INFORMATION

12.1 Eco toxicity: N/A

12.2 Degradability: N/A

12.3 Bioaccumulation Potential: N/A

12.4 Mobility in Soil: N/A

12.5 PBT & vPvB Assessment: N/A

12.6 Other Adverse Effects: N/A

#### 13. DISPOSAL CONSIDERATIONS

#### **Disposal Information:**

Dispose of product in accordance with local authority regulations.

Empty container retains product residue.

#### **Physical/Chemical Properties that affect Treatment:**

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

#### **Waste Treatment Information:**

If toner, do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

### **Personal Protection Required:**

N/A

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Revision date: 10/24/2017

Page: 6/9



Revision date: 10/24/2017

#### 14. TRANSPORT INFORMATION

**14.1 ID Number:** Classified as not a dangerous material. (IMO, ICAO, IATA).

14.2 Shipping Name: N/A

14.3 Hazard Class: N/A

14.4 Packing Group: N/A

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport: N/A

#### 15. REGULATORY INFORMATION

15.1 Regulatory Information: No specified regulation exists.

EPA Regulatory Information: N/A

**CERCLA Reportable Quantity: N/A** 

15.2 Superfund Information:

**Hazard Categories:** 

Immediate: N/A

Delayed: N/A

Fire: N/A

Pressure: N/A

Reactivity: N/A

Section 302 - Extremely Hazardous: N/A

Section 311 - Hazardous: N/A

15.3 State Regulations: N/A

15.4 Other Regulatory Information: N/A

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for **SATO Printers** 

Page: 7/9



## 16. OTHER INFORMATION

**General Comments:** This information is based on our current knowledge. It should not therefore be construed as

Revision date: 10/24/2017

guaranteeing specific properties of the products as described or their suitability for a particular

application

**Creation Date of this SDS:** 09/22/2020

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Page: 8/9



## Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	NIOSH = National Institute for Occupational Safety and Health
Hygienists	
CERCLA = Comprehensive Environmental Response Compensation	OSHA = Occupational Health and Safety Administration
and Liability Act	
CLP = Classification, Labeling, and Packaging	PEL = Permissible Exposure Limit
DSD = Dangerous Substances Directive	SCBA = Self Contained Breathing Apparatus
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity
GHS = Globally Harmonized System	TLV = Threshold Limit Value
N/A = Not Applicable	UK = United Kingdom
NFPA = National Fire Protection Association	UN = United Nations

	_4	С.
к	e	Г:

#### DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only. These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no

warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Revision date: 10/24/2017

Product: Enhanced Resin Ribbon 110mm x 410M (6 Ribbons/Case) for

**SATO Printers** 

Page: 9/9